

**DIMENSIONS:**

Load Capacity: 350 lbs

## EXTERIOR

Height - 32"  
Width - 56"  
Depth - 27 1/2"

## INTERIOR

Height - 17 1/2"  
Depth - 14"  
Rack to Glass - 1 7/8"  
Rack Width - 19"  
Rack Units - 10 RUs

SHIPPING BOX (Palletized)  
Length- 61"  
Width - 40"  
Height - 52"  
Ship Weight - 243 lbs



Available for immediate shipping

Ask about customized design  
and prototype capabilities

The GMP-200M is 32" tall and holds a single display up to 55". Comes standard with 10RU 19" rack mount bracket in front and rear, 6 port APC® surge protector, one adjustable shelf and has an interior depth of 14". Includes universal screen mounting system and set-top camera mount (TT-1).

Please include model number of screen when ordering.

**GMP - 200M - TT1****SOLID STEEL CARTS****The most FEATURES on the market:**

- ▶ One adjustable interior rack mounted shelf
- ▶ 6 Port APC® surge protector
- ▶ Cable management features
- ▶ Tempered, tinted locking front glass door
- ▶ Bolted rear panel for easy access to equipment
- ▶ Standard 19" front and rear rack mount brackets, 10RUs of space
- ▶ Standard adjustable v/c camera platform
- ▶ 32" height for optimal face-to-face communication
- ▶ Standard 4" double truck ball bearing casters, two with brake
- ▶ 100% Solid steel construction

**Choose your OPTIONS:**

- ▶ Additional rack mount shelf (US-1)
- ▶ Rack mounted M-Audio® speaker module (PSM-200)
- ▶ Heavy duty 6" caster upgrade
- ▶ Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ▶ GM-9000 to accommodate deeper equipment
- ▶ 6 Port rack mount APC® surge protector (RCK-PWR)
- ▶ Custom cut Rack Shelf for Lifesize®, Polycom® and Tandberg® codecs
- ▶ Revolabs® Shelving System in various configurations for wireless microphone integration

**Furniture Engineered For Today's Technology**